

01 GEMME LED COMPATTE FISSE FIXED LED GEMS DGA

# GEMMA 18


CON GHIERA  
WITH RING NUT

CON MOLLE  
WITH SPRINGS



Ottiche disponibili  
Available optics

Fotometrie  
Photometric data



\* E' necessario installare le gemme montando sotto la ghiera il dissipatore alettato a corredo.

\* It is necessary to install gemma by applying the included heat sink under the ring nut.

emissione 130°  
130° light emission





con ghiera \*  
with ring nut \*



codice ref	ottica optic	W	collegare a connect to
700100. _ _	130°	1	350mA
700101. _ _	2	500mA	

photometrics white LED		
5000K	4000K	3200K
B	Bn	Bw
B2	B2n	B2w



lente 40°  
40° lens



codice ref	ottica optic	W	collegare a connect to
740100. _ _	40°	1	350mA
740101. _ _	2	500mA	

D	Dn	Dw
D2	D2n	D2w

con molle  
with springs



codice ref	ottica optic	W	collegare a connect to
700108. _ _	130°	1	350mA

photometrics white LED		
5000K	4000K	3200K
B	Bn	Bw

740108. _ _	40°	1	350mA
-------------	-----	---	-------

D	Dn	Dw
---	----	----

LED colour  
Finiture/finishing

Finiture disponibili  
Finishing



Colore LED  
LED colour



## FEATURES

Ideal for displays\_watchmakers\_jewelleries\_museums\_showcases and retail application\_small dimensions\_quick installation\_modular and flexible\_cold\_neutral\_warm light\_not any heat emission on the products\_not any UV and IR radiation\_autonomy: 40'000 to 60'000 hours average\_consumption\_low consumption\_High power LED new generations : a better technology in the world.

## GUARANTEE

Guarantee\_2 years of factory guarantee\_all DCUBE products are built in compliance with the CE certification provided for the european directives and with the F certification for the installation on inflammable surface.