


03 APPARECCHI LED LINEARI LINEAR LED LIGHTING FIXTURES DGA

RIGA 3

ORIENTABILE  
ADJUSTABLE





Ottiche disponibili Available optics  
Fotometrie Photometric data



Tutte le plafoniere senza lenti sono disponibili, in esecuzione speciale, con grado di protezione IP54.  
All ceiling lamps without lenses are available upon request with IP54 protection rate.

emissione 130°  
130° light emission




| codice ref | L. mm | ottica optic | W       | collegare a connect to |
|------------|-------|--------------|---------|------------------------|
| 700287.3_  | 200   | 130°         | 3(3x1W) | 350mA                  |
| 700289.3_  |       |              | 6(3x2W) | 500mA                  |
| 700184.3_  | 375   |              | 3(3x1W) | 350mA                  |
| 700188.3_  |       |              | 6(3x2W) | 500mA                  |
| 700185.3_  | 450   |              | 3(3x1W) | 350mA                  |
| 700189.3_  |       |              | 6(3x2W) | 500mA                  |
| 740287.3_  | 200   | 40°          | 3(3x1W) | 350mA                  |
| 740289.3_  |       |              | 6(3x2W) | 500mA                  |
| 740184.3_  | 375   |              | 3(3x1W) | 350mA                  |
| 740188.3_  |       |              | 6(3x2W) | 500mA                  |
| 740185.3_  | 450   |              | 3(3x1W) | 350mA                  |
| 740189.3_  |       |              | 6(3x2W) | 500mA                  |

| photometrics white LED |       |       |
|------------------------|-------|-------|
| 5000K                  | 4000K | 3200K |
| F3                     | F3n   | F3w   |
| F6                     | F6n   | F6w   |
| F3                     | F3n   | F3w   |
| F6                     | F6n   | F6w   |
| F3                     | F3n   | F3w   |
| F6                     | F6n   | F6w   |
| G3                     | G3n   | G3w   |
| G6                     | G6n   | G6w   |
| G3                     | G3n   | G3w   |
| G6                     | G6n   | G6w   |
| G3                     | G3n   | G3w   |
| G6                     | G6n   | G6w   |

LED colour

lente 40°  
40° lens



Finiture disponibili Finishing  
grigio gray

Colore LED LED colour

5000K 1 3 5 4000K 9  
3200K 6

FEATURES

Ideal for displays\_watchmakers\_jewelleries\_museums\_showcases and retail application\_small dimensions\_quick installation\_modular and flexible\_cold\_neutral\_warm light\_not any heat emission on the products\_not any UV and IR radiation\_autonomy: 40'000 to 60'000 hours average\_consumption\_low consumption\_High power LED new generations : a better technology in the world.

GUARANTEE

Guarantee\_2 years of factory guarantee\_all DCUBE products are built in compliance with the CE certification provided for the european directives and with the F certification for the installation on inflammable surface.