

01 GEMME LED COMPATTE FISSE FIXED LED GEMS DGA


# GEMMA 30

CON GHIERA  
WITH RING NUT



Ottiche disponibili  
Available optics


Fotometrie  
Photometric data



E' necessario installare le gemme montando sotto la ghiera il dissipatore alettato a corredo.  
It is necessary to install gemma by applying the included heat sink under the ring nut.


vetro satinato  
frosted glass

sat.





vetro trasparente  
transparent glass

tra.



con ghiera  
with ring nut




codice ref	ottica optic	W	collegare a connect to
710102. _ _	sat.	1	350mA
720102. _ _	tra.	1	
710103. _ _	sat.	2	500mA
720103. _ _	tra.	2	
710524. _ _	sat.	2+	350mA
720524. _ _	tra.	2+	
710104. _ _	sat.	3	350mA
720104. _ _	tra.	3	
710608. _ 7	sat.	3	power supply RGB

photometrics white LED		
5000K	4000K	3200K
A	An	Aw
B	Bn	Bw
A2	A2n	A2w
B2	B2n	B2w
A2+	A2+n	A2+w
B2+	B2+n	B2+w
A3	A3n	A3w
B3	B3n	B3w




lente 10°  
10° lens



lente 30°  
30° lens



lente 60°  
60° lens



codice ref	ottica optic	W	collegare a connect to
730102. _ _	10°	1	350mA
760102. _ _	30°	1	
730103. _ _	10°	2	500mA
760103. _ _	30°	2	
760608. _ 7	30°	3	power supply RGB

C	Cn	Cw
R	Rn	Rw
C2	C2n	C2w
R2	R2n	R2w

codice ref	ottica optic	W	collegare a connect to
750102. _ _	60°	1	350mA
750103. _ _		2	
750524. _ _		2+	350mA
750104. _ _		3	


E	En	Ew
E2	E2n	E2w
E2+	E2+n	E2+w
E3	E3n	E3w

LED colour  
Finiture/finishing

Finiture disponibili  
Finishing



Colore LED  
LED colour



## FEATURES

Ideal for displays\_watchmakers\_jewelleries\_museums\_showcases and retail application\_small dimensions\_quick installation\_modular and flexible\_cold\_neutral\_warm light\_not any heat emission on the products\_not any UV and IR radiation\_autonomy: 40'000 to 60'000 hours average\_consumption\_low consumption\_High power LED new generations : a better technology in the world.

## GUARANTEE

Guarantee\_2 years of factory guarantee\_all DCUBE products are built in compliance with the CE certification provided for the european directives and with the F certification for the installation on inflammable surface.