

EOS plus

patent pending

10W
14W

con riflettore
with reflector


con lente
with lens

a sospensione
suspension

scala 1:1



con riflettore
with reflector



CODICE REF	OTTICA OPTIC	W	COLLEGARE A CONNECT TO	FINITURE DISPONIBILI FINISHING	TEMPERATURA COLORE LED K LED COLOUR TEMPERATURE K			PHOTOMETRICS		
					5000K	4000K	3200K	5000K	4000K	3200K
720547	rifi. 30°	10	220-240VAC	3	☑	☑	☑	B10	--	B10w
720587	rifi. 30°	14	220-240VAC		☐	☐	☑	B14	B14n	B14w
720669	rifi. 30°	10	220-240VAC		☐	☐	☐	B10	--	B10w
720671	rifi. 30°	14	220-240VAC		☐	☐	☐	B14	B14n	B14w

* E' possibile accorciare il cavo della sospensione o dell'asta rigida in fase di installazione.
 You can shorten the cable or the pole of the suspension at the moment of the installation.

FEATURES

Ideal for displays_watchmakers_jewelleries_museums_showcases and retail application_small dimensions_quick installation_modular and flexible_cold_neutral_warm light_not any heat emission on the products_not any UV and IR radiation_autonomy: 40'000 to 60'000 hours average_consumption_low consumption_High power LED new generations : a better technology in the world.

GUARANTEE

Guarantee_2 years of factory guarantee_all DCUBE products are built in compliance with the CE certification provided for the european directives and with the F certification for the installation on inflammable surface.