


EOS plus

patent pending

2x10W
2x14W
con riflettore
with reflector
con lente
with lens

per binario
track mounting



con riflettore
with reflector

con lente
with lens



L'apparecchio è fornito con attacco per BINARIO EUROSTANDARD.
The fixture is provided with connection for EUROSTANDARD TRACK

CODICE REF	OTTICA OPTIC	W	COLLEGARE A CONNECT TO	FINITURE DISPONIBILI FINISHING	TEMPERATURA COLORE LED K LED COLOUR TEMPERATURE K			PHOTOMETRICS			
					5000K	3000K	4000K	5000K	4000K	3200K	
720600. _ _	rifl. 30°	2x10	220-240VAC	3 4	☐	☐	☐	☐	☐	☐	B10 -- B10w
720602. _ _	rifl. 30°	2x14	220-240VAC	☐	☐	☐	☐	☐	☐	☐	B14 B14n B14w
780601. _ _	20°	2x10	220-240VAC	☐	☐	☐	☐	☐	☐	☐	C10 -- C10w
780603. _ _	20°	2x14	220-240VAC	☐	☐	☐	☐	☐	☐	☐	C14 C14n C14w

LED colour
Finitura/finishing

FEATURES

Ideal for displays_watchmakers_jewelleries_museums_showcases and retail application_small dimensions_quick installation_modular and flexible_cold_neutral_warm light_not any heat emission on the products_not any UV and IR radiation_autonomy: 40'000 to 60'000 hours average_consumption_low consumption_High power LED new generations : a better technology in the world.

GUARANTEE

Guarantee_2 years of factory guarantee_all DCUBE products are built in compliance with the CE certification provided for the european directives and with the F certification for the installation on inflammable surface.