


DA INCASSO
RECESSED


PER MONTAGGIO CON CASSAFORMA
FOR ASSEMBLY WITH HOUSING



Casseforme (Vedi cap.12)
Housings (See chap.12)



da incasso
recessed




codice ref	ottica optic	W	collegare a connect to
710163. _ _	sat.	1	350mA
720163. _ _	tra.		
730163. _ _	10°		
760163. _ _	30°		
710164. _ _	sat.	2	500mA
720164. _ _	tra.		
730164. _ _	10°		
760164. _ _	30°		

photometrics white LED		
5000K	4000K	3200K
A	An	Aw
B	Bn	Bw
C	Cn	Cw
R	Rn	Rw
A2	A2n	A2w
B2	B2n	B2w
C2	C2n	C2w
R2	R2n	R2w


LED colour
Finiture/finishing

Controcasse (Vedi cap.12)
Wallbox (See chap.12)




700163. _ _	130°	1	350mA
700164. _ _		2	500mA

B	Bn	Bw
B2	B2n	B2w



740163. _ _	40°	1	350mA
740164. _ _		2	500mA

D	Dn	Dw
D2	D2n	D2w



750163. _ _	60°	1	350mA
750164. _ _		2	500mA

E	En	Ew
E2	E2n	E2w

Finiture disponibili
Finishing



Colore LED
LED colour



FEATURES

Ideal for displays_watchmakers_jewelleries_museums_showcases and retail application_small dimensions_quick installation_modular and flexible_cold_neutral_warm light_not any heat emission on the products_not any UV and IR radiation_autonomy: 40'000 to 60'000 hours average_consumption_low consumption_High power LED new generations : a better technology in the world.

GUARANTEE

Guarantee_2 years of factory guarantee_all DCUBE products are built in compliance with the CE certification provided for the european directives and with the F certification for the installation on inflammable surface.